

H D S W 2 4 U L

24VDC HEAVY-DUTY VARIABLE SPEED SWING GATE OPERATOR

Ideal for heavy gate and extreme applications.



CONTINUOUS-DUTY OPERATION

DIRECT DRIVE GEAR BOX AND BRUSHLESS DC MOTOR
up to 6 million cycles

MOVE HEAVY GATES
up to 4,500 lbs. or 22 ft. length †

RELIABLE

CONTINUOUS-DUTY GATE OPERATION BUILT WITH A CUSTOM HEAVY-DUTY GEAR BOX, SIZE 80, DIRECT DRIVE 1,600:1 GEAR RATIO.

CUSTOM 1.5 HP PEAK BRUSHLESS DC MOTOR DELIVERS UP TO 6 MILLION CYCLES.

VARIABLE CYCLE SPEED ADJUSTS TO MEET APPLICATION NEEDS FROM 13 TO 36 SEC. FOR A 90-DEGREE OPENING.

SMOOTH START/STOP OPERATION AND MID-TRAVEL REVERSAL EXTEND OPERATOR HARDWARE LIFE.

STANDARD ARM (INCLUDED) MOVES GATES UP TO 2,800 LBS.

CUSTOM REINFORCED LONG ARM (OPTIONAL) MOVES GATES UP TO 4,500 LBS.

SMART

POWERED BY myQ® FOR FULL INSIGHT AND CONTROL OVER COMMUNITY AND FACILITY ACCESS POINTS. MONITOR AND CONTROL MULTIPLE COMMUNITIES WITH SMART COMMUNITY ACCESS. IMPROVE WAREHOUSE EFFICIENCY AND PRODUCTIVITY WITH SMART FACILITY ACCESS.*

FOUR PROGRAMMABLE AUXILIARY RELAYS ACCOMMODATE MORE ACCESSORIES.

WIRELESS DUAL-GATE COMMUNICATION SYNCHRONIZES GATE OPERATION AND ELIMINATES COSTLY TRENCHING; SET SPEED INDEPENDENTLY IF NEEDED.

SAFE AND SECURE

QUICK CLOSE AND ANTI-TAILGATE QUICKLY SECURES PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

POSILOCK® AUTOMATICALLY CLOSES THE GATE WHEN IT IS PUSHED FROM THE CLOSED LIMIT.

UL® LISTED GATE OPERATOR WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICE.

*When linked with an access control powered by myQ. Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

† Optional Reinforced Long Arm must be used to move 4,500 lb. or 22 ft. gates.

INCLUDED ACCESSORIES:

MONITORED RETRO-REFLECTIVE PHOTO EYE

Reliable retro-reflective photo eye with heater and wide beam, engineered to stay aligned; max. range: 50 ft.



LMRRUL

OPTIONAL & SAFETY ADD-ONS:

REINFORCED LONG ARM

For heavy gate applications of 2,500–4,500 lbs., 14–22 ft.

HDLGARM

MONITORED THROUGH-BEAM PHOTO EYES

Reliable through-beam with wide beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

MONITORED WIRELESS EDGE KIT

Low-energy Bluetooth® connection between a LiftMaster® Monitored Resistive Edge and the gate operator; max. range: 130 ft.



LMWEKITU

MONITORED RESISTIVE EDGES

Full line of Small and Large Profile Edges that sense obstructions.



EDGES

TOTAL SOLUTION ACCESSORIES:

CONNECTED ACCESS PORTAL WITH VIDEO

Cloud-based access control for residential communities.



CAPXLV

PLUG-IN LOOP DETECTOR

Prevents the gate from closing on a vehicle in the path; power efficient for maximum cycles on Battery Backup.



LOOPDETLM

INTERNET GATEWAY

Connects myQ-enabled gate operators to the Internet and enables control through the myQ app and communication to Access Control Systems powered by myQ.



828LM

PRODUCT GUIDE HDSW24UL

24VDC HEAVY-DUTY VARIABLE SPEED SWING GATE OPERATOR

LiftMaster®

MASTERFUL ENGINEERING.

MECHANICS



- 24VDC Brushless Continuous-Duty Motor
- **Operator Duty Rating:** High-Cycle, High-Temperature Continuous-Duty
- Direct Drive

POWER



- 120/240VAC Single-Phase
- **Accessory Power:** 24VDC 1 A Max. Output; Switched and Unswitched Power
- **Optional Kit (3PHCONV)** to Convert a 3-Phase Input Voltage of 208/240/480/575VAC to an Output Voltage of 120VAC
- **Solar-Ready, Ultra-Reliable System** Delivers Power When and Where You Need It (LMRRUL/LMTBUL Heater Option Not Recommended for Solar Applications)



COMMERCIAL-GRADE DESIGN



- **Chassis:** Constructed with 1/4 in. Steel, Powder Coated
- **Cover:** High-Density, UV-Resistant Polyethylene 2-Piece Cover for Excellent Heat and Corrosion Resistance
- **Warranty:** 5 Years Commercial, 7 Years Residential
- **UL® Usage Classification:** I, II, III and IV
- **Operator Weight:** 249 lbs.


28.04"




16.37"

19.59"

CAPACITIES
STANDARD ARM



CAPACITIES
LONG ARM



TEMPERATURE SPECIFICATIONS



- WITHOUT HEATER**
-4°F (-20°C) to 140°F (60°C)
- WITH OPTIONAL HEATER (HTR)**
-40°F (-40°C) to 140°F (60°C)



VARIABLE GATE SPEED
13–36 sec for a 90 degree opening

STANDARD FEATURES.

INHERENT REVERSING SENSOR

- Detects Obstructions and Reverses Gate

POSILOCK®

- Automatically Closes the Gate When It Is Pushed from the Closed Limit

MANUAL DISCONNECT

- Allows Gate to Be Opened Manually When Released

MONITORED SAFETY INPUTS

- 3 Main Board, 3 Expansion Board

SECURITY+ 2.0® ON-BOARD RADIO RECEIVER

- Up to 50 Remote Controls (Unlimited with 811LMX/813LMX)

LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

PROGRAMMABLE AUXILIARY RELAYS

- 4 Relays Make Adding Additional Features Easy

HOMELINK® COMPATIBLE

- Version 4.0 or Higher*

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.



SUPPORT.



For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information on Gate Operators, Visit LiftMaster.com/UL325Gates



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276